

Technical qualities:

Robust painted steel structure, with foldable side members for easy storage and transport.

Telescopic aluminum pole, for reduced space requirements and passage under standard door height.

Self-braking manual lifting winch with cable and double cranks.

4 swivel castors, 2 of which are equipped with brakes, as well as 2 additional wheels allowing easy movement in the folded position.

Available in 3 versions, LGM telescopic manual stackers can lift up to 350 kg of load to a height of 3.50 m or reach a height of 6.50 m with 250 kg.

Side stabilizers on the LGM-20 model.

As standard, LGM telescopic stackers are fitted with removable painted steel forks.

As an option, other accessories are available (stem, platform, cradle, ...).

Quick installation without tools.



Ref. 300752, 300753, 300754

LGM Telescopic Stackers are designed to move, lift and / or hold heavy loads to heights that can be important

- Robust and efficient
- Very simple manual operation
- Can be used by one person
- Versatile thanks to its accessories
- Compact shape optimizing its storage
- Foldable, it can easily be loaded and / or lying down in a commercial vehicle.

Applications:

- Industrial maintenance
- Installation of heating, air conditioning
- Installation of ventilation circuits
- Construction work, ...

Characteristics:

LGM-10	<ul style="list-style-type: none">· Maximum lifting height: 3,50 m· Maximum load capacity: 350 kg
LGM-15	<ul style="list-style-type: none">· Maximum lifting height: 5,00 m· Maximum load capacity: 300 kg
LGM-20	<ul style="list-style-type: none">· Maximum lifting height: 6,50 m· Maximum load capacity: 250 kg

Find the dimensional characteristics on the following page.

The maximum lifting height and load capacity of the stackers vary depending on the model: 3 versions available.

The forks can be installed in standard or inverted position to increase min / max lift heights.

The position of the load's center of gravity affects the load capacity of the stacker. Refer to the characteristics on the next page.

Models	LGM-10	LGM-15	LGM-20
References	300 752	300 753	300 754
Load capacities:			
Center of gravity of the load positioned at 400 mm	350 kg	300 kg	250 kg
Center of gravity of the load positioned at 600 mm	350 kg	300 kg	200 kg
Center of gravity of the load positioned at 800 mm	250 kg	250 kg	150 kg
Center of gravity of the load positioned at 1000 mm	150 kg	150 kg	100 kg
Maximum lifting heights:			
Forks in standard position	3020 mm	4560 mm	5850 mm
Forks in inverted position	3500 mm	5070 mm	6500 mm
Minimum lifting heights:			
Forks in standard position	140 mm		
Forks in inverted position	620 mm		
Dimensions:			
Total height in stowed position	2000 mm		
Ground clearance	50 mm		
Spar height	165 mm		
Spar spacing (inside / outside)	510 / 760 mm		
<i>Total length:</i>			
• In transport position	880 mm		
• In working position	1640 mm	2200 mm	2200 mm
<i>Total width:</i>			
• Without side stabilizers	800 mm		
• With side stabilizers	-	1800 mm	1800 mm
Fork section (H x W)	60 x 40 mm		
Fork length	700 mm		
Fork spacing (inside / outside)	420 / 500 mm		
Empty mass:	118 kg	144 kg	184 kg

Accessories:

<i>Supplied as standard</i>	<i>Optional</i>	<i>Optional</i>	<i>Optional</i>
Forks (ref. 300 876)	Cradle (ref. 300 875)	Platform (ref. 300 877)	Crane arm (ref. 300 874)

Terms of use

The user is responsible for defining the products to be adapted to its own use. TELIP takes charge of submitting accurate and updated information. However, as part of the continuous improvement of its products, TELIP reserves the right to proceed with frequent modifications without warning. Therefore, TELIP cannot guarantee the accuracy and current reality of information on its products. All transactions are subject to general terms and conditions of sales and transportation. These conditions are available upon request and downloadable on the website www.telip.fr.

TELIP
MANUTENTION ET LEVAGE

TELIP
2, rue Andrée Reigner - Z. I. La Bougeoire
35 130 La Guerche de Bretagne
FRANCE

Tél. : 02 99 96 17 16
Fax : 02 99 96 17 26

contact@telip.fr
www.telip.fr